

72 Fiber Optic Outdoor Horizontal Splice Closure

Splice Trays Included – 6 Ports at 12mm (x2) 20mm (x2) and 25mm (x2)

Overview

Fibertronics Inc. offers horizontal splice closures designed to protect and manage spliced fiber optic cables in a variety of network environments. These closures provide a sealed, durable housing that shields fiber splices from moisture, dust, and extreme temperatures. Suitable for aerial, underground, and direct-burial applications, they are built to ensure long-term reliability in harsh conditions. Fibertronics' designs also support easy installation and high fiber capacity, making them ideal for both small and large-scale fiber networks.



Key Features

- All performance indicators meet GR-771-CORE standards
- · Suitable for aerial, wall-mount, or direct burial applications
- IP68 Rated Dustproof and water-resistant
- Corrosion and UV resistant

Typical Applications

- · Underground, aerial, and direct-buried fiber optic splicing
- · Outside Plant (OSP) fiber network deployments
- FTTx (FTTH, FTTB, FTTC) rollout and maintenance
- Telecommunications and ISP backbone networks

Technical Specifications

Ports	6 Ports
Splice Capacity	72 Fibers
Max. Splice Capacity	144 Fibers
Splice Trays Included	3 Trays
Splice Tray Capacity	6 Trays
Cable Diameter	2x Ф16mm max. / 2x Ф20mm max. / 2x Ф23mm max.
Closure Size	450mm x 216mm x 160mm
IP Rating	IP68
Sealing Type	Mechanical
Internal Components Material	ABS
Metal Accessories Material	Stainless Steel



