

# WTB-FWM-6102 2 LGX, Wall Mount Patch Panel with Single Door

**FIBERTRONICS** 





## The WTB-FWM-6102 is a high density wall-mount fiber optic enclosure.

The unit has 2 adapter panel positions allowing for a wide range of fiber termination connector types. It is equipped with a set of keys that allow access to the network side of the panel. A padlock can be added to the outer door which allows access to the disribution side, maintaining seperation and security between the network and distribution sides of the termination panel.

### **Product Features**

- 2 LGX Adapter Panels
- 1 Slack Spool
- High Density
- Powder Coated

- 1 Outer Door with Padlock Option (Padlock not included)
- 1 Inner Door with Keyed Lock
- Screw Holes on the rear panel

### **Technical Specifications**

Below are the specifications of this wall-mountable, fiber optic patch panel. These include patch panel positions, ports, dimensions and materials.

Capacity	2 LGX Adapter Panels
Port	4 Port - Ø25mm (0.98")
Lockable	Yes
Туре	Single Door
Material	16 Gauge Powder Coated Steel
Height	259mm (10.2")
Width	305mm (12.0")
Depth	89mm (3.5")
Weight	3.39kg (7.47lbs)
Color	Black

#### Accessories

Below is a list of the accessories that are included with this product.

Keys:	2
Cable Ties:	5
Grommets:	4
Cable Management Rings:	5
Laser Warning Labels:	1
Location Label:	1
Grounding Screw:	1

Please Note: Mounting hardware is not included.