



WTB-FWM-6104 4 LGX, Wall Mount Patch Panel with Single Door

FIBERTRONICS 



The WTB-FWM-6104 is a high density wall-mount fiber optic enclosure.

The unit has 4 adapter panel positions allowing for a wide range of fiber termination connector types. Equipped with a set of keys that allow access to the network side of the panel. If required a padlock can be added to the outer door allowing access to the distribution side, maintaining separation & security between the network & distribution sides of the panel.

Product Features

- 4 LGX Adapter Panels
- 2 Slack Spools
- High Density
- Powder Coated
- 1 Outer Door with padlock option (Padlock not included)
- 1 Inner Door with keyed lock
- Screw Holes on the rear panel

Technical Specifications

Below are the specifications of this wall-mountable, fiber optic patch panel. These include patch panel positions, ports, dimensions and materials.

Capacity	4 LGX Adapter Panels
Port	4 Port - Ø25mm (0.98")
Lockable	Yes
Type	Single Door
Material	16 Gauge Powder Coated Steel
Height	305mm
Width	305mm
Depth	89mm
Weight	3.94kg (8.68lbs)
Color	Black
Weight	4.94kg (10.89lbs)
Color	Black

Accessories

Below is a list of the accessories that are included with this product.

Keys:	2
Cable Ties:	5
Grommets:	4
Laser Warning Labels:	1
Location Label:	1
Grounding Screw:	1

Please Note: Mounting hardware is not included.