



WTB-FWM-6209 9 LGX, Wall Mount Patch Panel with 2 Doors

FIBERTRONICS 



The WTB-FWM-6209 is a high density wall-mount fiber optic enclosure designed to support patching & splicing in one unit.

The unit has 9 adapter panel positions allowing for a wide range of fiber termination connector types. It is equipped with a set of keys that allow access to the network side of the panel. If required a padlock can be added to the distribution side, maintaining separation and security between the network and distribution sides of the termination panel.

Product Features

- 9 LGX Adapter Panels
- 4 Slack Spools
- High Density
- Powder Coated
- 2 Outer Doors
- Network Side Door is Key Locked
- Distribution Side Door with Padlock Option (Padlock not included)
- Screw Holes on the Rear Panel

Technical Specifications

Below are the specifications of this wall-mountable, fiber optic patch panel. These include patch panel positions, ports, dimensions and materials.

Capacity	9 LGX Adapter Panels
Port	8 Port - Ø25mm (0.98")
Splice Trays Included	0 (Supports 1)
Supported Splice Trays	TRAY-X1, TRAY-X2, TRAY-X3, TRAY-X4, FT-TRAY12, FT-TRAY12AL, FT-TRAY24, FT-TRAY24AL, FT-SET12
Lockable	Yes
Type	Double Doors
Material	16 Gauge Powder Coated Steel
Height	440mm (17.5")
Width	540mm (21.0")
Depth	128mm (5.0")
Weight	8.12kg (17.90lbs)
Color	Black

Accessories

Below are the specifications of this wall-mountable, fiber optic patch panel. These include patch panel positions, ports, dimensions and materials.

Keys:	2
Cable Ties:	5
Grommets:	8
Laser Warning Labels:	1
Location Label:	1
Grounding Screw:	1

Please Note: Mounting hardware is not included.